


ALL DESIGN, OPERATIVE AND PROCESS DATA PERTAINING TO THE ARTICLE SHOWN ON THIS SHEET IS THE PROPERTY OF POLYPHASER CORPORATION. THE INFORMATION IS NOT TO BE COPIED, REPRODUCED, REVEALED TO OR APPROPRIATED BY OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF POLYPHASER CORPORATION.

These commodities or technology are exported from the U.S. in accordance with the Export Administration Regulations. Diversion contrary to U.S. law prohibited.

REVISIONS

REV LTR	DATE	ENG	MKTG	Q.A.
A	06/10/03 RD	JJ	SD	LJ
B	07/26/04 RD	LC	WO	LJ
C	INC ECN 2595 ^{CM}	AD		



MAXIMUM CHARACTERISTICS

APPLICATION:

BULKHEAD MOUNT
WEATHERPROOF WHEN INSTALLED

SURGE / FREQUENCY / VSWR:

IEC 61000-4-5 8/20 μ s WAVEFORM
20kA @ 800MHz TO 2.0GHz @ $\leq 1.1:1$ VSWR
18kA @ 800MHz TO 2.3GHz @ $\leq 1.1:1$ VSWR
18kA @ 700MHz TO 2.7GHz @ $\leq 1.2:1$ VSWR

INSERTION LOSS:

≤ 0.1 dB

CONTINUOUS POWER:

500W @ 920MHz
(750W @ 50°C)

LET THROUGH VOLTAGE:

$\leq \pm 3$ VOLTS FOR 3kA @ 8/20 μ s WAVEFORM

THROUGHPUT ENERGY:

$\leq 0.5\mu$ J FOR 3kA @ 8/20 μ s WAVEFORM

TEMPERATURE:

-40°C TO +85°C STORAGE/OPERATING

VIBRATION:


1G @ 5Hz TO 100Hz

ENVIRONMENTAL:

MEETS IEC 60529 IP65
MEETS BELLCORE #TA-NWT-000487
PROCEDURE 4.11, WIND DRIVEN (120MPH)
RAIN INTRUSION TEST

CUSTOMER APPROVAL: _____ DATE: _____

ALL DIMENSIONS SHOWN ABOVE ARE FOR REFERENCE ONLY.

DRAFTER I. BENNETT	DATE 10/18/02	 P.O. BOX 9000 MINDEN, NV 89423 TEL: 775-782-2511 FAX: 775-782-4476 DWG NO/PART NO/DESCRIPTION DSXL CUSTOMER PRINT		
MECH ENGINEER R. DUNNING	DATE 10/21/02			
ELEC ENGINEER J. JONES	DATE 10/21/02			
MARKETING S. DOTTER	DATE 10/21/02			
QUALITY DEPT L. JACQUES	DATE 10/21/02			
CAGE CODE 61114	FILE NAME -C1	SCALE 1/1	SHEET 1 OF 1	