




ALL DESIGN, OPERATIVE AND PROCESS DATA PERTAINING TO THE ARTICLE SHOWN ON THIS SHEET IS THE PROPERTY OF POLYPHASER CORPORATION. THE INFORMATION IS NOT TO BE COPIED, REPRODUCED, REVEALED TO OR APPROPRIATED BY OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF POLYPHASER CORPORATION.

REVISIONS

REV LTR	DATE	ENG	MKTG	Q.A.
---------	------	-----	------	------




MAXIMUM CHARACTERISTICS

APPLICATION:
 BULKHEAD MOUNT
 WEATHERPROOF WHEN INSTALLED
 SURGE:
 20kA IEC 1000-4-5 8/20 μ s WAVEFORM
 FREQUENCY RANGE:
 1.2GHz TO 2.8GHz
 VSWR:
 $\leq 1.1:1$
 INSERTION LOSS:
 ≤ 0.1 dB
 CONTINUOUS POWER:
 300W
 LET THROUGH VOLTAGE:
 $\leq \pm 3$ VOLTS FOR 3kA @ 8/20 μ s WAVEFORM
 THROUGHPUT ENERGY:
 $\leq 0.5\mu$ J FOR 3kA @ 8/20 μ s WAVEFORM
 TEMPERATURE:
 -40°C TO +85°C STORAGE/OPERATING
 VIBRATION:
 1G AT 5Hz TO 100Hz
 ENVIRONMENTAL:
 MEETS IEC 60529 IP65.
 MEETS BELLCORE #TA-NWT-000487
 PROCEDURE 4.11, WIND DRIVEN (120MPH)
 RAIN INTRUSION TEST.

CUSTOMER APPROVAL: _____ DATE: _____

ALL DIMENSIONS SHOWN ABOVE ARE FOR REFERENCE ONLY.

DRAFTER R. DUNNING	DATE 12/19/02	 P.O. BOX 9000 MINDEN, NV 89423 TEL: 775-782-2511 FAX: 775-782-4476 PSXL-MA CUSTOMER PRINT	
MECH ENGINEER R. DUNNING	DATE 02/10/03		
ELEC ENGINEER J. JONES	DATE 01/30/03		
MARKETING S. DOTTER	DATE 02/10/03		
QUALITY DEPT L. JACQUES	DATE 02/10/03		
CAGE CODE 61114	FILE NAME -C1	SCALE 1/1	SHEET 1 OF 1