


ALL DESIGN, OPERATIVE AND PROCESS DATA PERTAINING TO THE ARTICLE SHOWN ON THIS SHEET IS THE PROPERTY OF POLYPHASER CORPORATION. THE INFORMATION IS NOT TO BE COPIED, REPRODUCED, REVEALED TO OR APPROPRIATED BY OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF POLYPHASER CORPORATION.

REVISIONS

REV LTR	DATE	ENG	MKTG	Q.A.
---------	------	-----	------	------



MAXIMUM CHARACTERISTICS

APPLICATION:

BULKHEAD, WEATHERPROOF WHEN INSTALLED

SURGE:

25kA IEC 61000-4-5 8/20 μ s WAVEFORM

FREQUENCY RANGE:

350MHz TO 1.2GHz @ 1.1:1VSWR

INSERTION LOSS:

≤ 0.1 dB

CONTINUOUS POWER @ 450MHz:

1kW @ 85°C

1.5kW @ 40°C

2kW @ 20°C

LET THROUGH VOLTAGE:

$\leq \pm 3$ VOLTS FOR 3kA @ 8/20 μ s WAVEFORM

THROUGHPUT ENERGY:

$\leq 0.5\mu$ J FOR 3kA @ 8/20 μ s WAVEFORM

VIBRATION:

1G @ 5Hz TO 100Hz

TEMPERATURE:

-40°C TO +85°C STORAGE/OPERATING

ENVIRONMENTAL:

MEETS BELLCORE #TA-NWT-000487


PROCEDURE 4.11, WIND DRIVEN (120MPH)

RAIN INTRUSION TEST.

MEETS IEC 60529 IP65.

CUSTOMER APPROVAL: _____ DATE: _____

ALL DIMENSIONS SHOWN ABOVE ARE FOR REFERENCE ONLY.

DRAFTER R. SWART	DATE 02/23/05	 P.O. BOX 9000 MINDEN, NV 89423 TEL: 775-782-2511 FAX: 775-782-4476 DWG NO/PART NO/DESCRIPTION USXL-D CUSTOMER PRINT	
MECH ENGINEER R. DUNNING	DATE 05/17/05		
ELEC ENGINEER J. JONES	DATE 05/12/05		
MARKETING S. DOTTER	DATE 05/16/05		
QUALITY DEPT L. JACQUES	DATE 05/16/05		
CAGE CODE 61114	FILE NAME -C1	SCALE 1/1	SHEET 1 OF 1